

Desde ui.macc.unican.es utilizaremos el comando kpasswd o el nativo de Unix passwd.

```
#####método 1
[ui ~]$passwd
Changing password for user ferprobando.
Kerberos 5 Password:
New Kerberos 5 Password:
Repeat New Kerberos 5 Password:
passwd: all authentication tokens updated successfully.

#####método 2
[ui ~]kpasswd
Password for ferprobando@MACC.UNICAN.ES:
Enter new password:
Enter it again:
Password changed.
```

## Política del AD

Complejidad de la clave:

- 3 tipos de caracteres(minusculas, mayusculas, dígitos, o caracteres no alfabéticos)
- no contener mas de dos caracteres consecutivos del nombre de la cuenta.

## En caso de que la contraseña caduque

Al conectarnos por ssh nos pedirá cambiarla

```
root@seal:~# ssh ferprobando@ui.macc.unican.es
ferprobando@ui.macc.unican.es's password:
**Warning: password has expired.**
Last login: Thu Jun  8 13:07:52 2017 from seal.macc.unican.es
WARNING: Your password has expired.
You must change your password now and login again!
Changing password for user ferprobando.
Kerberos 5 Password:
New Kerberos 5 Password:
Repeat New Kerberos 5 Password:
passwd: all authentication tokens updated successfully.
Connection to ui.macc.unican.es closed.
```

\*