

Wikiprint Book

Title: Data Publishing

Subject: TracMeteo - ESGFCordexDataPublication

Version: 21

Date: 07/23/2021 10:01:01 PM

Table of Contents

Data Publishing	3
Configuring a new project for ESGF publication	3
Using the ESGF Publisher	6
File Scan Phase	6
Generate a THREDDS catalog	7
idx notification	7
Running all publication steps	8
Access files	8
v20140328	9

Data Publishing

Configuring a new project for ESGF publication

See the [?ESGF](#) publication reference for details.

In order to publish, you have to configure a text file, `/esg/config/esgcat/esg.ini`. For this propose, we are going to create a new project called `cordex`:

```
[initialize]
log_level = DEBUG
initial_models_table = /esg/config/esgcat/esgcat_models_table.txt

[DEFAULT]
thredds_dataset_roots =
    esg_dataroot | /datasets

project_options =
    cordex | CORDEX Output data | 1
[project:cordex]
#     name | category_type | is_mandatory | is_thredds_property | display_order
categories =
    project          | enum | true | true | 0
    domain           | enum | true | true | 1
    institute        | enum | true | true | 2
    driving_model    | enum | false | true | 3
    experiment       | enum | false | true | 4
    ensemble         | enum | false | true | 5
    model            | enum | false | true | 6
    time_frequency   | enum | false | true | 7
    version          | enum | false | true | 8
    rcm_model        | enum | false | true | 9
    rcm_version      | enum | false | true | 10
    description      | text | false | false | 99
category_defaults =
    domain | EUR-22
    institute | UCAN
    driving_model | ERAINT
    ensemble | rli1p1
    model | WRF331G
    time_frequency | mon
dataset_id = cordex.%(domain)s.%(institute)s.%(driving_model)s.%(experiment)s.%(ensemble)s.WRF331G_v02.%(time_frequency)s.
directory_format = /datasets/CORDEX/output/%(domain)s/%(institute)s/%(driving_model)s/%(experiment)s/%(ensemble)s/%(rcm_model)s
domain_map = map(project_id,domain : domain_description)
    cordex | SAM-44 | South America
    cordex | CAM-44 | Central America
    cordex | NAM-44 | North America
    cordex | EUR-44 | Europe
    cordex | EUR-22 | Europe
    cordex | AFR-44 | Africa
    cordex | WAS-44 | West Asia
    cordex | EAS-44 | East Asia
    cordex | CAS-44 | Central Asia
    cordex | AUS-44 | Australasia
    cordex | ANT-44 | Antarctica
    cordex | ARC-44 | The Arctic
    cordex | MED-44 | HYMEX Mediterranean
    cordex | EUR-11 | High-res. Europe
    cordex | SAM-44i | South America
    cordex | CAM-44i | Central America
```

```

cordex | NAM-44i | North America
cordex | EUR-44i | Europe
cordex | AFR-44i | Africa
cordex | WAS-44i | West Asia
cordex | EAS-44i | East Asia
cordex | CAS-44i | Central Asia
cordex | AUS-44i | Australasia
cordex | ANT-44i | Antarctica
cordex | ARC-44i | The Arctic
cordex | MED-44i | HYMEX Mediterranean
cordex | EUR-11i | High-res. Europe
cordex | MNA-44  | Middle East and North Africa
cordex | MNA-44i | Middle East and North Africa
cordex | MNA-22  | Middle East and North Africa
cordex | MNA-22i | Middle East and North Africa
domain_options = SAM-44,CAM-44,NAM-44, EUR-44, EUR-22, EUR-44i, AFR-44, AFR-44i, WAS-44, EAS-44, CAS-44, AUS-44, ANT-44, ARC-44, MED-44
driving_model_options = ERAINT, ECMWF-ERAINT, CCCma-CanESM2, CNRM-CERFACS-CNRM-CM5, ICHEC-EC-EARTH, MIROC-MIROC5, MOHC-HadGEM2-ES
ensemble_options = r1i1p1, r12i1p1, r0i0p0
experiment_options =
  cordex | evaluation | no description
  cordex | historical  | no description
  cordex | rcp4        | no description
  cordex | rcp26       | no description
  cordex | rcp45       | no description
  cordex | rcp85       | no description
institute_map = map(project_id,model : institute)
  cordex | WRF331G | UCAN
institute_options = UCAN
las_configure = false
las_time_delta_map = map(time_frequency : las_time_delta)
  mon   | 1 month
  day   | 1 day
  fx    | fixed
  sem   | semi
maps = institute_map, las_time_delta_map, domain_map
model_options = WRF331G
parent_id = wdcc2.cordex
project_handler_name = basic_built_in
rcm_model_options = UCAN-WRF331G
rcm_version_options = v02
thredds_exclude_variables = a, a_bnds, alev1, alevel, alevhalf, alt40, b, b_bnds, basin, bnds, bounds_lat, bounds_lon, dbz
time_frequency_options = day, fx, mon, sem, 3hr, 6hr
variable_locate = ps,ps_ | vas,vas_ | uas,uas_ | tasmin,tasmin_ | tasmax,tasmax_ | tas,tas_ | sfcWindmax,sfcWindmax_ | sfcWind
variable_per_file = true
version_options = 20131108

```

Therefore, if you use the above configuration file, you will have to create a tree directory like this:

```

[esgf@data datasets]# tree
.
|-- CORDEX
  |-- output
    |-- EUR-22
      |-- UCAN
        |-- ECMWF-ERAINT
          |-- evaluation
            |-- r1i1p1
              |-- UCAN-WRF331G
                |-- v02
                  |-- 3hr
                    |-- hfls

```

```

|-- 20131108
|   |-- hfsls_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_3hr_19790101
|   |-- hfsls_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_3hr_20100101
|-- hfss
|   |-- 20131108
|   |-- hfss_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_3hr_19790101
|   |-- hfss_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_3hr_19800101
|   |-- hfss_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_3hr_20100101
|-- huss
|   |-- 20131108
|   |-- huss_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_3hr_19790101
|   |-- huss_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_3hr_19800101
|   |-- huss_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_3hr_20100101
|-- pr
|   |-- 20131108
|   |-- pr_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_3hr_19790101
|   |-- pr_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_3hr_20100101
|-- prc
|   |-- 20131108
|   |-- prc_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_3hr_19790101
|   |-- prc_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_3hr_20100101
|-- ps
|   |-- 20131108
|   |-- ps_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_3hr_19790101
|   |-- ps_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_3hr_20100101
|-- rlds
|   |-- 20131108
|   |-- rlds_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_3hr_19790101
|   |-- rsds_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_3hr_20090101
|   |-- rsds_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_3hr_20100101
|-- sfcWind
|   |-- 20131108
|   |-- sfcWind_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_3hr_19790101
|   |-- sfcWind_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_3hr_19800101
|   |-- sfcWind_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_3hr_20090101
|   |-- sfcWind_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_3hr_20100101
|-- tas
|   |-- 20131108
|   |-- tas_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_3hr_19790101
|   |-- tas_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_3hr_20100101
|-- 6hr
|   |-- mrros
|   |-- 20131108
|   |-- mrros_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_6hr_19790101
|   |-- mrros_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_6hr_20090101
|   |-- mrros_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_6hr_20100101
|-- uas
|   |-- 20131108
|   |-- uas_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_6hr_19790101
|   |-- uas_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_6hr_20090101
|   |-- uas_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_6hr_20100101
|-- vas
|   |-- 20131108
|   |-- vas_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_6hr_19790101
|   |-- vas_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_6hr_20090101
|   |-- vas_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_6hr_20100101
|-- day
|   |-- mrso
|   |-- 20131108
|   |-- mrso_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_day_19790101
|   |-- mrso_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_day_20060101

```

```

| |-- pr
| |  |-- 20131108
| |    |-- pr_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_day_19790101-
| |    |-- pr_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_day_20060101-
| |  |-- sfcWindmax
| |    |-- 20131108
| |      |-- sfcWindmax_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_day_1
| |      |-- sfcWindmax_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_day_2
| |      |-- sfcWindmax_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_day_2
| |  |-- tasmx
| |    |-- 20131108
| |      |-- tasmx_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_day_19790
| |      |-- tasmx_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_day_20060
| |  |-- tasmin
| |    |-- 20131108
| |      |-- tasmin_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_day_19790
| |      |-- tasmin_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_day_20060
|-- mon
  |-- pr
  |  |-- 20131108
  |    |-- pr_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_mon_19790101-
  |    |-- pr_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_mon_20010101-
  |-- tas
  |  |-- 20131108
  |    |-- tas_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_mon_19790101
  |    |-- tas_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_mon_19910101
  |    |-- tas_EUR-22_ECMWF-ERAINT_evaluation_rlilpl_UCAN-WRF331G_v02_mon_20010101

```

Then you have to add the project name to the `esgcat_models_table.txt` file

```
$ echo "  cordex | WRF331G | http://meteo.unican.es | UNICAN WRF3.3.1 Model version, 2.0" >> /esg/config/esgcat/esgcat_mon
```

After modifying `esgcat_models_table.txt` and `esg.ini` files, you have to update the data base by executing :

```
$ cd /usr/local/uvcdat/1.4.0/bin/
$ ./esginitialize -i /esg/config/esgcat/esg.ini -c
```

- `./esginitialize -d 0`: To remove all tables
- `./esginitialize -c`: Upgrade the database schema to the latest version, and initialize projects, models, experiments, and standard names from configuration files.

Using the ESGF Publisher

This takes place in three steps:

- Scan each file for metadata and save the metadata in the node database. (This is in contrast to running `esgscan_directory`, which just scans the directory structure.)
- Generate a THREDDS catalog based on the scanned information. THREDDS is a data and metadata server used by ESGF.
- Notify the idx that one or more catalogs have been generated.

File Scan Phase

In order to scan the `cordex` files for metadata, run `esgscan_directory` to generate a mapfile and after that run `esgpublish` with input from a mapfile:

```
$ whoami
esgf
$ cd /usr/local/uvcdat/1.4.0/bin
```

```

$ ./esgscan_directory -i /esg/config/esgset/esg.ini --project cordex -o ~/cordex.txt /datasets/CORDEX
$ sudo ./esgpublish -i /esg/config/esgset/esg.ini --map ~/cordex.txt

```

In order to check that the datasets were entered correctly into the database, list the datasets for cordex project:

```

$ ./esglist_datasets -i /esg/config/esgset/esg.ini cordex
+-----+-----+-----+-----+-----+-----+
| id | name | project | model | experiment | run |
+-----+-----+-----+-----+-----+-----+
| 1 | cordex.EUR-22.UCAN.ECMWF-ERAINT.evaluation.rlilpl.WRF331G_v02.3hr.hfls | cordex | WRF331G | evaluation | Non |
| 2 | cordex.EUR-22.UCAN.ECMWF-ERAINT.evaluation.rlilpl.WRF331G_v02.3hr.hfss | cordex | WRF331G | evaluation | Non |
| 3 | cordex.EUR-22.UCAN.ECMWF-ERAINT.evaluation.rlilpl.WRF331G_v02.3hr.huss | cordex | WRF331G | evaluation | Non |
| 4 | cordex.EUR-22.UCAN.ECMWF-ERAINT.evaluation.rlilpl.WRF331G_v02.3hr.pr | cordex | WRF331G | evaluation | Non |
| 5 | cordex.EUR-22.UCAN.ECMWF-ERAINT.evaluation.rlilpl.WRF331G_v02.3hr.prc | cordex | WRF331G | evaluation | Non |
| 6 | cordex.EUR-22.UCAN.ECMWF-ERAINT.evaluation.rlilpl.WRF331G_v02.3hr.ps | cordex | WRF331G | evaluation | Non |
| 7 | cordex.EUR-22.UCAN.ECMWF-ERAINT.evaluation.rlilpl.WRF331G_v02.3hr.rlds | cordex | WRF331G | evaluation | Non |
| 8 | cordex.EUR-22.UCAN.ECMWF-ERAINT.evaluation.rlilpl.WRF331G_v02.3hr.rsds | cordex | WRF331G | evaluation | Non |
| 9 | cordex.EUR-22.UCAN.ECMWF-ERAINT.evaluation.rlilpl.WRF331G_v02.3hr.sfcWind | cordex | WRF331G | evaluation | Non |
| 10 | cordex.EUR-22.UCAN.ECMWF-ERAINT.evaluation.rlilpl.WRF331G_v02.3hr.tas | cordex | WRF331G | evaluation | Non |
| 11 | cordex.EUR-22.UCAN.ECMWF-ERAINT.evaluation.rlilpl.WRF331G_v02.6hr.mrros | cordex | WRF331G | evaluation | Non |
| 12 | cordex.EUR-22.UCAN.ECMWF-ERAINT.evaluation.rlilpl.WRF331G_v02.6hr.uas | cordex | WRF331G | evaluation | Non |
| 13 | cordex.EUR-22.UCAN.ECMWF-ERAINT.evaluation.rlilpl.WRF331G_v02.6hr.vas | cordex | WRF331G | evaluation | Non |
| 14 | cordex.EUR-22.UCAN.ECMWF-ERAINT.evaluation.rlilpl.WRF331G_v02.day.mrso | cordex | WRF331G | evaluation | Non |
| 15 | cordex.EUR-22.UCAN.ECMWF-ERAINT.evaluation.rlilpl.WRF331G_v02.day.pr | cordex | WRF331G | evaluation | Non |
| 16 | cordex.EUR-22.UCAN.ECMWF-ERAINT.evaluation.rlilpl.WRF331G_v02.day.sfcWindmax | cordex | WRF331G | evaluation | Non |
| 17 | cordex.EUR-22.UCAN.ECMWF-ERAINT.evaluation.rlilpl.WRF331G_v02.day.tasmax | cordex | WRF331G | evaluation | Non |
| 18 | cordex.EUR-22.UCAN.ECMWF-ERAINT.evaluation.rlilpl.WRF331G_v02.day.tasmin | cordex | WRF331G | evaluation | Non |
| 19 | cordex.EUR-22.UCAN.ECMWF-ERAINT.evaluation.rlilpl.WRF331G_v02.mon.pr | cordex | WRF331G | evaluation | Non |
| 20 | cordex.EUR-22.UCAN.ECMWF-ERAINT.evaluation.rlilpl.WRF331G_v02.mon.tas | cordex | WRF331G | evaluation | Non |
+-----+-----+-----+-----+-----+-----+

```

In order undo the scan, run esgunpublish with the following flags:

```

$ ./esgunpublish -i /esg/config/esgset/esg.ini --skip-gateway --skip-thredds --database-delete --map ~/cordex.txt

```

Generate a THREDDS catalog

You can generate the THREDDS catalog with :

```

$ sudo ./esgpublish -i /esg/config/esgset/esg.ini --project cordex --map ~/cordex.txt --noscan --thredds
INFO      2013-11-19 19:46:30,642 Writing THREDDS catalog /esg/content/thredds/esgset/1/cordex.EUR-22.UCAN.ECMWF-ERAINT.e
INFO      2013-11-19 19:46:30,837 Writing THREDDS catalog /esg/content/thredds/esgset/1/cordex.EUR-22.UCAN.ECMWF-ERAINT.e
INFO      2013-11-19 19:46:31,019 Writing THREDDS catalog /esg/content/thredds/esgset/1/cordex.EUR-22.UCAN.ECMWF-ERAINT.e
INFO      2013-11-19 19:46:31,198 Writing THREDDS catalog /esg/content/thredds/esgset/1/cordex.EUR-22.UCAN.ECMWF-ERAINT.e
INFO      2013-11-19 19:46:31,536 Writing THREDDS catalog /esg/content/thredds/esgset/1/cordex.EUR-22.UCAN.ECMWF-ERAINT.e
.....

```

In order to remove the catalogs from the THREDDS :

```

$ ./esgunpublish -i /esg/config/esgset/esg.ini --map ~/cordex.txt --skip-gateway

```

idx notification

First, obtain a digital certificate from an ESGF trusted MyProxy server, and rename it to whatever path you have defined in esg.ini.

Remember, you have to log in a Federation to do it.

```

$ sudo /usr/local/globus/bin/myproxy-logon -s vesgint-idx.ipsl.jussieu.fr -l blancojc -o ~/.globus/certificate-file

```

Then you can publish the cordex catalog by executing :

```
$ sudo ./esgpublish -i /esg/config/esgcat/esg.ini --project cordex --map ~/cordex.txt --noscan --publish
INFO      2013-11-19 20:01:24,817 Publishing: cordex.EUR-22.UCAN.ECMWF-ERAINT.evaluation.r1ilpl.WRF331G_v02.3hr.hfls
INFO      2013-11-19 20:01:28,678 Result: SUCCESSFUL
INFO      2013-11-19 20:01:28,678 Publishing: cordex.EUR-22.UCAN.ECMWF-ERAINT.evaluation.r1ilpl.WRF331G_v02.3hr.hfss
INFO      2013-11-19 20:01:32,416 Result: SUCCESSFUL
INFO      2013-11-19 20:01:32,417 Publishing: cordex.EUR-22.UCAN.ECMWF-ERAINT.evaluation.r1ilpl.WRF331G_v02.3hr.huss
INFO      2013-11-19 20:01:36,125 Result: SUCCESSFUL
INFO      2013-11-19 20:01:36,125 Publishing: cordex.EUR-22.UCAN.ECMWF-ERAINT.evaluation.r1ilpl.WRF331G_v02.3hr.pr
INFO      2013-11-19 20:01:39,964 Result: SUCCESSFUL
INFO      2013-11-19 20:01:39,965 Publishing: cordex.EUR-22.UCAN.ECMWF-ERAINT.evaluation.r1ilpl.WRF331G_v02.3hr.prc
```

Use esgunpublish to delete idx datasets:

```
$ ./esgpublish -i /esg/config/esgcat/esg.ini --map ~/cordex.txt --skip-thredds
```

Running all publication steps

For convenience, the full publication can be performed with one command. Also, if the arguments are directories rather than a mapfile, the directories will be scanned as if esgscan_directory were run:

```
$ sudo ./esgpublish -i /esg/config/esgcat/esg.ini --project cordex --map ~/cordex.txt --noscan --thredds
INFO      2013-11-19 19:46:30,642 Writing THREDDS catalog /esg/content/thredds/esgcat/1/cordex.EUR-22.UCAN.ECMWF-ERAINT.e
INFO      2013-11-19 19:46:30,837 Writing THREDDS catalog /esg/content/thredds/esgcat/1/cordex.EUR-22.UCAN.ECMWF-ERAINT.e
INFO      2013-11-19 19:46:31,019 Writing THREDDS catalog /esg/content/thredds/esgcat/1/cordex.EUR-22.UCAN.ECMWF-ERAINT.e
```

esgunpublish will remove the datasets from the idx, THREDDS, and node database in that order:

```
$ sudo ./esgpublish -i /esg/config/esgcat/esg.ini --database-delete --map ~/cordex.txt
```

Access files

Finally, in order to grant access to our files you need to add the line below :

```
<policy resource=".*CORDEX.*" attribute_type="ANY" attribute_value="" action="Read"/>
```

in your esgf_policies_local.xml file :

```
$ cat /usr/local/apache-tomcat-7.0.47/webapps/esg-orp/WEB-INF/classes/esg-orp/orp/config/esgf_policies_local.xml
<?xml version="1.0" encoding="UTF-8" standalone="yes"?>

<!-- This file is intended to be edited and maintained by the local Node administrators.
It should contain only policies specific to data served by the local Node.
It will not be overridden by a software update. -->
<policies xmlns="http://www.esgf.org/security">
  <policy resource=".*CORDEX.*" attribute_type="ANY" attribute_value="" action="Read"/>
  <!-- The following statements allow all members of group "CMIP5 Research" or "CMIP5 Commercial" to read any local URL t
Note that the groups "CMIP5 Research" and "CMIP5 Commercial" are administered by PCMDI -->
  <!-- <policy resource=".*cmip5.*" attribute_type="CMIP5 Research" attribute_value="user" action="Read"/> -->
  <!-- <policy resource=".*cmip5.*" attribute_type="CMIP5 Commercial" attribute_value="user" action="Read"/> -->
  <!-- These statements provide CMIP5 Read access for members of the old gateways -->
  <!-- <policy resource=".*cmip5.*" attribute_type="CMIP5 Research" attribute_value="default" action="Read"/> -->
  <!-- <policy resource=".*cmip5.*" attribute_type="CMIP5 Commercial" attribute_value="default" action="Read"/> -->

  <!-- The following statement allows all members of group "MY GROUP" to read any local URL that contains "my_data"
  <policy resource=".*my_data.*" attribute_type="MY GROUP" attribute_value="user" action="Read"/> -->
```



```

<!-- The following statement allows members of group "MY GROUP" with role="publisher" to publish local datasets with id
<policy resource=".*my_data.*" attribute_type="MY GROUP" attribute_value="publisher" action="Write"/> -->

<!-- The following statements makes resources that contain '.*test.*' freely available for download -->
<!-- <policy resource=".*test.*" attribute_type="ANY" attribute_value="" action="Read"/> -->

<!-- The following statements makes all resources freely available for download -->
<!-- <policy resource=".*" attribute_type="ANY" attribute_value="" action="Read"/> -->

</policies>

```

In production status, you will have to something like this:

```

<policy resource=".*CORDEX.*" attribute_type="CORDEX_Research" attribute_value="user" action="Read"/>
<policy resource=".*CORDEX.*" attribute_type="CORDEX_Research" attribute_value="default" action="Read"/>
<policy resource=".*CORDEX.*" attribute_type="CORDEX_Commercial" attribute_value="user" action="Read"/>
<policy resource=".*CORDEX.*" attribute_type="CORDEX_Commercial" attribute_value="default" action="Read"/>

```

v20140328