

Wikiprint Book

Title: ESGF Local Node Deployment Tutorial

Subject: TracMeteo - ESGFNodeTutorial

Version: 47

Date: 07/07/2022 04:11:23 AM

Table of Contents

ESGF Local Node Deployment Tutorial	3
Index	3
0. Prerequisites	3
1. Previous installation clean up	3
2. Installation from scratch	4
Configuration for publishing	7
Publish the test dataset	8
Publish CORDEX datasets	9
Known issues during installation	9
#error "Pycopg requires PostgreSQL client library (libpq) >= 9.1	9
Failed building wheel for Pillow	10
Installing a custom certificate in the ESGF Node	10
References	10


```

Sending stop command to Solr running on port 8984 ... waiting 5 seconds to allow Jetty process 16554 to stop gracefully.
Stopping Globus Services for Data-Node... (GridFTP) stop_globus_services for datanode
globus-gridftp-server: unrecognized service
Stopping Globus Services for Index-Node... (MyProxy server) stop_globus_services for gateway
Stopping myproxy-server:                                [ OK ]
No MyProxy Process Currently Running...
Tomcat (jsvc) process is running...

stop tomcat: /usr/local/tomcat/bin/jsvc -pidfile /var/run/tomcat-jsvc.pid -stop org.apache.catalina.startup.Bootstrap
(please wait)
postmaster (pid 16024) is running...
Stopping postgresql service:                            [ OK ]
Stopping httpd:                                        [ OK ]
Running shutdown hooks...

-----
Running Node Services...
node type: [ data index idp compute ] (60)
-----
-----

```

Execute source /usr/local/bin/esg-purge.sh && esg-purge all

2. Installation from scratch

Change directory to /usr/local/bin/

```
[root@spock ~]# cd /usr/local/bin/
```

```

[root@spock bin]# wget -O esg-bootstrap http://distrib-coffee.ipsl.jussieu.fr/pub/esgf/dist/devel/esgf-installer/2.4/esg-b
[root@spock bin]# chmod 555 ./esg-bootstrap
[root@spock bin]# ./esg-bootstrap

```

Your directory should look like this:

```

[root@spock bin]# ls
esg-bootstrap  esg-functions  esg-init  esg-node  esg-purge.sh  jar_security_scan  setup-autoinstall

```

Check your node's version:

```

[root@spock bin]# ./esg-node --version
Version: v2.4.24-master-release
Release: Bifrost
Earth Systems Grid Federation (http://esgf.llnl.gov)
ESGF Node Installation Script

```

Set node's type:

```

[root@spock bin]# ./esg-node --set-type data idp index
node type set to: [ index data idp ] (28)

```

Install the node:

```
[root@spock bin]# ./esg-node --install
```

Please select the ESGF distribution mirror for this installation (fastest to slowest):

```

-----
[1] http://dist.ceda.ac.uk/esgf

```

```

[2] http://esg-dn2.nsc.liu.se/esgf
[3] http://aims1.llnl.gov/esgf
[4] http://distrib-coffee.ipsl.jussieu.fr/pub/esgf
-----
select [1] > 1

```

```

Are you ready to begin the installation? [Y/n]
Configured host IP address does not match available IPs...
Detected multiple IP addresses bound to this host...
Please select the IP address to use for this installation
-----
[0] : 193.xxx.xxx.xxx
[1] : 192.xxx.xxx.xxx
-----
select [] > (select the one that fits your case)

```

```

Welcome to the ESGF Node installation program! :-)

What is the fully qualified domain name of this node? [spock.meteo.unican.es]:
What is the admin password to use for this installation? (alpha-numeric only) []:
Please re-enter password:
What is the name of your organization? [unican]:
Please give this node a "short" name: []: unican
Please give this node a more descriptive "long" name []: unican
What is the namespace to use for this node? (set to your reverse fqdn - Ex: "gov.llnl") [es.unican.meteo]:
What peer group(s) will this node participate in? (esgf-test|esgf-prod) [esgf-test]:
What is the default peer to this node? [spock.meteo.unican.es]:
What is the hostname of the node do you plan to publish to? [spock.meteo.unican.es]:
What email address should notifications be sent as? []:
Is the database external to this node? [y/N]:
Please enter the database connection string...
(form: postgresql://[username]@[host]:[port]/esgct)
What is the database connection string? [postgresql://dbsuper@localhost:5432/esgct]: postgresql://
entered: postgresql://dbsuper@localhost:5432/esgct
What is the (low priv) db account for publisher? [esgct]:
What is the db password for publisher user (esgct)? []:

```

```

Enter password for postgres user dbsuper:
Re-enter password for postgres user dbsuper:
Please Enter PostgreSQL port number [5432]:>

```

```

Would you like a "system" or "user" publisher configuration:
-----
*[1] : System
[2] : User
-----
[C] : (Custom)
-----
select [1] >

You have selected: 1
Publisher configuration file -> [/esg/config/esgct/esg.ini]

Is this correct? [Y/n]
Your publisher configuration file will be: /esg/config/esgct/esg.ini
What is your organization's id? [unican]:

```

```

Would you like to use the DN: (OU=ESGF.ORG, O=ESGF) ? [Y/n]:
...

```

Please enter the password for this keystore :

Enter a single ip address which would be cleared to access admin restricted pages.
You will be prompted if you want to enter more ip-addresses

Do you wish to allow further ips? y/n
n

Create user credentials
Please enter username for tomcat [dnode_user]:
Please enter password for user, "dnode_user" [*****]:
Would you like to add another user? [y/N]:

Please Enter the public (i.e. routable) IP address of this host [193.xxx.xxx.xxx]:>
Do you wish to use an external IDP peer?(N/y):

Do you want to continue with the Globus installation and setup? [Y/n] :
Do you want to register the MyProxy server with Globus? [Y/n]:
Please provide a Globus username []: YOUR-GLOBUS-USER
Globus password []:

When finished, you should see something like this:

```
Running Node Services...
node type: [ data index idp ] (29)
-----
myproxy-s 23071    root    5u  IPv4 1526752      0t0  TCP *:7512 (LISTEN)
java      26088    solr   28u  IPv6 1591850      0t0  TCP 127.0.0.1:7983 (LISTEN)
java      26088    solr   92u  IPv6 1591986      0t0  TCP *:8983 (LISTEN)
java      26257    solr   28u  IPv6 1592730      0t0  TCP 127.0.0.1:7984 (LISTEN)
java      26257    solr   92u  IPv6 1593098      0t0  TCP *:8984 (LISTEN)
postmaste 29509    postgres 3u  IPv6 1449862      0t0  TCP [::1]:5432 (LISTEN)
postmaste 29509    postgres 4u  IPv4 1449863      0t0  TCP 127.0.0.1:5432 (LISTEN)
httpd     12706    root    4u  IPv6 1512235      0t0  TCP *:80 (LISTEN)
-----

Finished!...
In order to see if this node has been installed properly you may direct your browser to:
http://spock.meteo.unican.es/thredds
http://spock.meteo.unican.es/esg-orp
http://spock.meteo.unican.es/

Your peer group membership -- : [esgf-test]
Your specified "default" peer : [spock.meteo.unican.es]
Your specified "index" peer - : [spock.meteo.unican.es] (url = http://spock.meteo.unican.es/)
Your specified "idp" peer --- : [spock.meteo.unican.es] (name = SPOCK.METEO.UNICAN.ES)
Your temporary certificates have been placed in /etc/tempcerts
You can install them by executing this : esg-node --install-keypair /etc/tempcerts/hostcert.pem /etc/tempcerts/hostkey.pem
When prompted for the chainfile, specify: /etc/tempcerts/cacert.pem

[Note: Use UNIX group permissions on /esg/content/thredds/esgcert to enable users to be able to publish thredds catalogs fr
%> chgrp -R <appropriate unix group for publishing users> /esg/content/thredds

-----

Administrators of this node should subscribe to the
esgf-node-admins@lists.llnl.gov by sending email to: majordomo@lists.llnl.gov
with the body: subscribe esgf-node-admins
```

```
-----
```

```
v2.4.24-master-release
```

```
Writing additional settings to db. If these settings already exist, psql will report an error, but ok to disregard.
ERROR: insert or update on table "permission" violates foreign key constraint "permission_user_id_fkey"
DETAIL: Key (user_id)=(1) is not present in table "user".
Node installation is complete.
```

Execute the following:

```
[root@spock bin]# ./esg-node --install-keypair /etc/tempcerts/hostcert.pem /etc/tempcerts/hostkey.pem
...
Please set the password for this keystore  :
Please re-enter the password for this keystore:
...
certfile> /etc/tempcerts/cacert.pem
certfile>
...
Is the above information correct? [Y/n]
Is the above information correct? [Y/n]
```

Restart the node:

```
[root@spock bin]# ./esg-node restart
```

Check that everything works ([?https://github.com/ESGF/esgf-installer/wiki/ESGF-Post-Installation-Tests](https://github.com/ESGF/esgf-installer/wiki/ESGF-Post-Installation-Tests)).

If the CoG portal does not work follow the instructions on [?https://www.earthsystemcog.org/projects/cog/install_or_upgrade](https://www.earthsystemcog.org/projects/cog/install_or_upgrade).

Now you should be able to log in the CoG portal using the openid "[?https://spock.meteo.unican.es/esgf-idp/openid/rootAdmin](https://spock.meteo.unican.es/esgf-idp/openid/rootAdmin)" and the password that you chose in the installation process.

Configuration for publishing

The installation process should have created a user in the postgres database, named rootAdmin. You can check it by running `psql -U dbsuper -d esgset` (to access the postgres cli) and visualizing the table `esgf_security.user`.

```
esgset=# select * from esgf_security.user;
 id |  firstname  |  middlename  |  lastname  |  email  |  username  |  password  |  dn  |
-----+-----+-----+-----+-----+-----+-----+-----+
 1 | Admin      |              | User       | emailOfTheAdmin | rootAdmin | hashOfThePassword |      |
-b50e-d43692adc5e5 |          |              |              |              |              |              |      |
 https://domain/esgf-idp
```

In order to test the publication, create a new user using the CoG web interface ([?https://\[index_node_fgdn\]](https://[index_node_fgdn])). You should click on 'Create Account' and fill the form. Once the user is created using the CoG interface, it should be visible in the `esgf_security.user` table of the postgres database.

```
esgset=# select * from esgf_security.user;
 id |  firstname  |  middlename  |  lastname  |  email  |  username  |  password  |  dn  |
-----+-----+-----+-----+-----+-----+-----+-----+
 1 | Admin      |              | User       | emailOfTheAdmin | rootAdmin | hashOfThePassword |      |
-b50e-d43692adc5e5 |          |              |              |              |              |              |      |
 2 | zequi      |              | cimadevilla | emailOfZequi   | zequi     | hashOfThePassword |      |
```

Once the user is created, create permissions and roles as follows:

(reference documentation - [?https://acme-climate.atlassian.net/wiki/display/ESGF/Guide+to+ESGF+Publishing+and+Best+Practices](https://acme-climate.atlassian.net/wiki/display/ESGF/Guide+to+ESGF+Publishing+and+Best+Practices))

```

esgctl=# select * from esgf_security.role;
id | name | description
-----+-----+-----
1 | super | Super User
2 | none | None
3 | default | Standard
4 | publisher | Data Publisher
5 | admin | Group Administrator
6 | user | user role
(6 rows)

esgctl=# select * from esgf_security.group;
id | name | description | visible | automatic_approval
-----+-----+-----+-----+-----
1 | wheel | Administrator Group | t | t
2 | test_group | test group | t | t
3 | cordex_group | cordex group | t | t
(3 rows)

esgctl=# select * from esgf_security.permission;
user_id | group_id | role_id | approved
-----+-----+-----+-----
2 | 2 | 4 | t
2 | 2 | 6 | t
2 | 3 | 6 | t
2 | 3 | 4 | t
(4 rows)

```

Add the following elements to /esg/config/esgf_policies_local.xml

```

<policy resource=".*test.*" attribute_type="test_group" attribute_value="user" action="Read"/>
<policy resource=".*test.*" attribute_type="test_group" attribute_value="publisher" action="Write"/>
<policy resource=".*cordex.*" attribute_type="cordex_group" attribute_value="user" action="Read"/>
<policy resource=".*cordex.*" attribute_type="cordex_group" attribute_value="publisher" action="Write"/>

```

Add the following elements to /esg/config/esgf_ats_static.xml

```

<attribute
  type="test_group"
  attributeService="https://spock.meteo.unican.es/esgf-idp/saml/soap/secure/attributeService.htm"
  description="Test group for test data"
  registrationService="https://spock.meteo.unican.es/esgf-idp/secure/registrationService.htm"/>

<attribute
  type="cordex_group"
  attributeService="https://spock.meteo.unican.es/esgf-idp/saml/soap/secure/attributeService.htm"
  description="Test group for cordex data"
  registrationService="https://spock.meteo.unican.es/esgf-idp/secure/registrationService.htm"/>

```

Generate your credentials for publication - globus certificate

```
myproxy-logon [ -b ] -s <openid_server> -l <your_esgf_username> -p 7512 -t 72 -o $HOME/.globus/certificate-file
```

The certificate is valid for 72 hours when specified by -t. If you are publishing for the first time, you will need to mkdir \$HOME/.globus and use -b to bootstrap its trustroots with the server. The esgf_username is the simply the username portion of your openid rather than the entire openid string, e.g. sashakames, not [?https://pcmdi.llnl.gov/esgf-idp/openid/sashakames](https://pcmdi.llnl.gov/esgf-idp/openid/sashakames)

Publish the test dataset


```
https://github.com/ESGF/esgf.github.io/wiki/ESGFNode%7CFAQ
```

Failed building wheel for Pillow

This error seems unavoidable but it also seems that it doesn't affect the esgf functionality.

Installing a custom certificate in the ESGF Node

You should own your certificate file (hostcert.crt) and your private key (hostkey.key). Your /etc/httpd/conf/esgf-httpd.conf must reference your certificate and key:

```
228     SSLVerifyClient optional
229     SSLVerifyDepth 10
230     SSLCertificateFile /etc/certs/hostcert.crt
231     #SSLCACertificateFile /etc/certs/esgf-ca-bundle.crt
232     SSLCertificateKeyFile /etc/certs/hostkey.key
233     #SSLCertificateChainFile /etc/certs/cachain.pem
234     SSLOptions +StdEnvVars +ExportCertData
```

Then you have to import your certificate and your key into your tomcat keystore (located in /esg/config/tomcat/ and named esg-truststore.ts and keystore-tomcat). They are configurated in /usr/local/tomcat/conf/server.xml.

1. If the self-signed certificate is installed in keystore-tomcat, remove it with `keytool -delete -alias ALIAS -keystore keystore-tomcat`, where alias can be obtained with `keytool -v -list -keystore keystore-tomcat`.
1. Execute `# openssl pkcs12 -export -in /etc/certs/hostcert.crt -inkey /etc/certs/hostkey.key -out server.p12 -name my-esgf-node -CAfile /etc/certs/hostcert.crt -caname root and keytool -importkeystore -deststorepass PASSWORD -destkeypass PASSWORD -destkeystore keystore-tomcat -srckeystore server.p12 -srcstoretype PKCS12 -srcstorepass PASSWORD -alias my-esgf-node`
1. Ensure it has been correctly installed with `keytool -v -list -keystore keystore-tomcat`.
1. Restart the node: `esg-node restart`
1. More info in [?Stackoverflow](#)

References

- [?ESGF Installation From Scratch](#)