

Wikiprint Book

Title: ESGFToolsUI

Subject: TracMeteo - ESGFToolsUI

Version: 106

Date: 12/02/2021 01:27:11 AM

Table of Contents

What is ESGF Tools UI?	3
Getting started	3
Pre-requisites	3
Installation	3
Search of ESGF Climate Data	3
Selecting a index node	4
Selecting search parameters	4
Selecting search parameters: Tree of parameters	5
Selecting search parameters: drop-down list of parameters	5
Selecting search parameters: configured parameters	6
Using free text search	6
Save a search	7
Select a saved search	7
Reset search panel	7
Metadata Harvesting of ESGF Datasets of a search	7
What is a ESGF Dataset?	8
Search Harvesting Panel	8
Exploring search harvesting	9
Exploring search harvesting : Harvesting view	10
Exploring search harvesting : Open metadata	11
Exploring search harvesting : Download Dataset - File selection window	11
Export to Metalink	12
Download a Search	12
Download of ESGF Datasets	14
ESGF Login : Obtaining credentials with ESGF Account	15
Join a group with the needed permissions for a unauthorized file	16

What is ESGF Tools UI?

A tool that is integrated in [?ToolsUI NetCDF Java](#) for including a desktop client for [?ESGF services](#), with features like search of data along multiple nodes, download manager and metadata aggregation for allowing a full exploration through dataset services.

The added functionality in ToolsUI NetCDF is in ESGF tab. This tab contains 4 sub-tabs, each one with an specific functionality.



Getting started

Pre-requisites

JDK from Sun / Oracle (1.5 - newer) or OpenJDK 6

OpenJDK 7 is not supported

Installation


1. Download the zip in [ESGFToolsUI-0.4.1.zip](#)
2. Unzip it
3. Go to unzipped directory
 - In Windows:
 - Open ESGFToolsUI.jar
 - In Linux
 - In shell:

```
java -jar ESGFToolsUI.jar
```


Search of ESGF Climate Data

A search in ESGF returns the records that matching the search constraints after querying to an index node. The ESGF search service is always served by a index node and this node is able to do local and distributed searches. In this tool, the distributed capabilities of the ESGF are used so any selected index node will be used to query all nodes in the ESGF system.

The search panel of ESGF climate data is in the "Search" sub-tab (be patient, the panel takes to load). The search constraints are defined by parameter configuration in the panel or by introduction of a free-text search query. The result are the number of records finding in the federation that satisfy the constraints of search (in panel in bottom right area). Record is the physical replica of a climate dataset that are stored on a data node.



Selecting a index node




The searches are executed in a index node of the federation. Each node have different processing times for the response. For this reason, the user is allowed to select the index node where prefers send the search petition. The index node may be configured in the top left drop-down list. After selected a new index node the search panel is updated.

Selecting search parameters

The search parameters can be configured on the panel in two ways:

- By values selection in tree of parameters double click
- By parameter selection in drop-down list



Selecting search parameters: Tree of parameters

The tree of parameters shows the parameters with bounded values which are defined by the federation. In the first level is the name of the parameter and the number of its bounded values. In the second level are the parameter values, each one with the count of records that satisfy the previous configured constraints (restrictions that are listed in the "configured parameters" section) + the new constraint (parameter-value).

For each parameter can be selected more than one value doing double click in the checkbox. Finally, for adding the selected values on the tree in the search constraints you must click on "Add parameters" button. All values selected in a parameter are linked by logic OR and the selected parameters are linked by logic AND. Generally, the parameter configuration is as follows, where "P" is a parameter and "V" a value.

$$[(P_1 - V_1) \vee (P_1 - V_2) \vee \dots \vee (P_1 - V_n)] \wedge [(P_2 - V_1) \vee (P_2 - V_2) \vee \dots \vee (P_2 - V_n)] \\ \wedge [(P_n - V_1) \vee (P_n - V_2) \vee \dots \vee (P_n - V_n)]$$

For example, if are selected:

```
* Institute
* BNU ?
* CCCMA ?
* Model
* BNU-ESM ?
```

Then the result will be the number of records that belong to BNU-ESM model and made by BNU or CCCMA institutes i.e.
 $((\text{Institute}, \text{BNU}) \vee (\text{Institute}, \text{CCCMA})) \wedge ((\text{Model}, \text{BNU-ESM}))$

After adding new parameters the search panel is updated (?Add parameters? button). Now in the tree, all parameters that already have values configured only shows this values. This happens because the allowed values ??for a parameter are always those that do not result in an empty set if they are selected. To configure a parameter previously configured you can uncheck the previously configured values and then click on "Add parameters" or you can remove them in "Configured parameters" section.

Selecting search parameters: drop-down list of parameters

The parameter selection in drop-down list (top right) allows values configuration of some parameters. In this list are contained the parameters without bounded values and that for this reason can't be configured in the tree of parameters. Also contains the parameters with bounded values. After selecting a list parameter, below of the list will be displayed a specific configuration panel for the selected parameter.

In the figure below you can see the panel that is displayed when ?temporal range of data coverage? is selected. Finally, to be added this configuration click in the bottom button "Add parameter" ("Add temporal range parameter" in this case).

Temporal range of data coverage (Start-End)

Select temporal range of data coverage (Start-End)

start

enero 1920

	lun	mar	mié	jue	vie	sáb	dom
01				1	2	3	4
02	5	6	7	8	9	10	11
03	12	13	14	15	16	17	18
04	19	20	21	22	23	24	25
05	26	27	28	29	30	31	

end

enero 2000

	lun	mar	mié	jue	vie	sáb	dom
52						1	2
01	3	4	5	6	7	8	9
02	10	11	12	13	14	15	16
03	17	18	19	20	21	22	23
04	24	25	26	27	28	29	30
05	31						

Add temporal range parameter

Selecting search parameters: configured parameters

All configured parameters are displayed in a specific panel in bottom left. In this panel are listed the configured parameters with its values assigned.

In the figure below can see that the current search is configured for searching climate data that belong to CMIP5 project, that were made by BNU or CCCMA institute, that have a time frequency of six hours, belongs to "historical" experiment and that have data between 15-01-1920 and 20-01-2000, and finally contains at least one of this variables: "hus", "ps", "psl", "ta".

Configured parameters:

Project : [CMIP5]
 end:2000-01-20T11:40:49Z
 start:1920-01-15T11:40:49Z
 Experiment : [historical]
 Variable : [hus, ps, psl, ta]
 Institute : [BNU, CCCMA]
 Time frequency : [6hr]

Remove
Remove all

This panel also allow to select a parameter and delete its configuration doing click on "Remove" and delete all parameters configuration doing click on "Remove all"

Using free text search

The free-text search o full text search allows to do a search rich in syntax, by arbitrary words, logic operations and wild-cards. In this case, the records searched will be records that contains metadata that are related with what is specified in the free text query.

In top center in the search panel can see the text box where can be introduced the query of free text search. The "Edit" button enables input by keyboard in the text box. The "Save" button adds the free text query parameter in the search. The new configured parameter will be displayed in the "configured parameters" section with the name "query".

Search
Search Harvesting
Downloads
Login

esgf-index1.ceda.ac.uk
Free text:
R (id:*IPSL* AND (model:IPSL-CM5A-LR OR model:IPSL-CM5B-LR))

Save
Hist

The free-text query may have:

- Logic operations (AND & OR) between words
- Wildcard * for the words
- Parentheses () as separators

- `metadata_name:word` to specify the metadata name where must match the given word

For example, the query:


```
institute:CCCMA OR (id:*IPSL* AND (model:IPSL-CM5A-LR OR model:IPSL-CM5B-LR))
```

Will search all records in ESGF whose institute is CCCMA OR that satisfy the following points:

1. Have an id that contains the word IPSL (`id:*IPSL*`)
2. Belong to IPSL-CM5A-LR model OR IPSL-CM5B-LR model

Save a search


A configured search can be saved for later for to be able do a harvesting of metadata and services of datasets that satisfy the search constraints. The save section is in right bottom of search panel. You can overwrite the selected search with "Save search" button or save it with a new name clicking on "Save Search As..." button.



The name of search must be unique. Duplicated names aren't allowed

Select a saved search

You can select a previously saved search from the right top drop-down list. After select a search, the search panel is updated.



Reset search panel

To restart the search panel must be selected in the drop-down list the option: `<<New search>>`

Metadata Harvesting of ESGF Datasets of a search

The metadata harvesting will allow, after completed, download the datasets from multiple data nodes, and will allow exploring climate datasets without having to download the dataset itself . So we can know its nature in detail before selecting them to download or we can know the services offered from ESGF to access and/or explore the dataset. Some of these services can be explored from ToolsUI NetCDF Java as will be explained after.

The harvesting are doing at `dataset` level.

The screenshot shows the NetCDF (4.3) Tools interface. The main menu includes System, Modes, Debug, and Help. Below the menu are tabs for Viewer, Writer, NCDump, Iosp, CoordSys, FeatureTypes, THREDDS, Fmrc, GeoTiff, Units, NcML, URLdump, and ESGF. The Search Harvesting tab is active, showing a list of search entries. Each entry includes search parameters, harvesting progress, and control buttons.

Search Name	Harvesting Progress	Files Harvested	Files Total	Size Harvested	Size Total	Status	Buttons
(No name)	100%	29/29	2333/4851	3,5 TB	7,1 TB	Completed	Explore search, Export to Metalink, Download ...
IPSL-CM5A-LR(1980-1990)-zosga	100%	18/18	18/774	232,0 KB	101,0 GB	Completed	remove, reset, Explore search, Export to Metalink, Download ...
IPSL-Historical(CORDEX)	39%	36/92	186/186	65,5 GB	65,5 GB so far	In Progress	pause, remove, reset, Explore search

What is a ESGF Dataset?

Dataset is a climate data in a specific version stored by ESGF. One dataset may have several records i.e. the records are the physical replica of a dataset in a data node.

Also, the datasets are formed of files, i.e. dataset are a virtual container of data, so that the information is contained in files and sometimes in aggregations. The versions of datasets are generated when errors are found in the datasets giving rise to a new corrected version.

Datasets, files and aggregations have replicas in data nodes. And the ESGF services (THREDDS, LAS, HTTP, GridFTP and OPeNDAP) are always served at replicas level. That is the reason why the harvesting must be done before the download.

Search Harvesting Panel

The harvesting panel may be selected clicking on the sub-tab "Search Harvesting". In this panel are deployed a list of searches and their harvesting states. Also, provides several options for flow control, complete exploration of harvested datasets and the possibility to do a manual selection of files to put them in download queue.

Each harvesting for a search is an element in the list deployed in the harvesting panel. In the figure below can see one search harvesting. In the left are the search data (name of search and configured parameters). In the right are the state data of the harvesting and the flow options, also shows the number of files that are selected from the total number of files and their sizes in bytes.

One harvesting is always of a completed dataset (with all files). However, a search may include only some files of the total in a dataset (e.g a search with less variables that there is in the dataset or a search in a range of time). That is why, by default, the files selected to future downloads (in the application or by generation of metalink) are always the files that satisfy ALL search constraints.

Noteworthy that this application allows to manually select files to download in case that you want to download files that are not selected by default or deselected some of these.

The flow control options are below progress bar:

- start - start the harvesting
- pause - pause the harvesting
- remove - remove the search and its harvesting (but the harvesting remains in file system)
- reset - remove all data of harvesting in file system and put the state of harvesting to zero)

In the center bottom there are the options to explore and download the harvested datasets:

Explore Search	is always visible and allows explore and put to download a individual dataset. Also, view a individual state of harvesting of a dataset
Export to metalink	is visible when harvesting of search is completed. Allows to generate a metalink file with the files and its resources (replicas in data nodes)
Download ...	is visible when harvesting of search is completed. Allows to put to download all files that satisfy the constraints of the search or to put to download a set of files manually selected of the search

Exploring search harvesting

To exploring the search harvesting of a search you must click on `Explore Search` option that is always visible in harvesting panel. And then a window pops up with the exploring options.

This window provides a paginated list of harvesting states of datasets that belong to the search. Each dataset are identify by its `instance_id`. The last value comma separated is the version of dataset. The exploring options in this window are provided at dataset level. Each dataset have options, and these are only provided when the dataset harvesting is completed.

In ESGF the dataset are identify by `id`, `instance_id` and `master_id`. And in this application the "instance_id" is the more important because identify all replicas across federation and is specific to each version.

For more information [?https://github.com/ESGF/esgf.github.io/wiki/ESGF_Search_REST_API#identifiers](https://github.com/ESGF/esgf.github.io/wiki/ESGF_Search_REST_API#identifiers)

In figure below can see the exploring window and its options.

Dataset: cordex.output.EUR-11.IPSL-INERIS.IPSL-IPSL-CM5A-MR.historical.r1i1p1.WRF331F.v1.mon.rlus.v20140301			
Completed	size: 188,5 MB	Harvesting View	Open metadata
Download dataset...			
Dataset: cordex.output.EUR-44.IPSL-INERIS.IPSL-IPSL-CM5A-MR.historical.r1i1p1.WRF331F.v1.mon.pr.v20140301			
Completed	size: 15,2 MB	Harvesting View	Open metadata
Download dataset...			
Dataset: cordex.output.EUR-11.IPSL-INERIS.IPSL-IPSL-CM5A-MR.historical.r1i1p1.WRF331F.v1.mon.rsdtd.v20140301			
Harvesting...			
Dataset: cordex.output.EUR-11.IPSL-INERIS.IPSL-IPSL-CM5A-MR.historical.r1i1p1.WRF331F.v1.day.sfcWindmax.v20140301			
Harvesting...			
Dataset: cordex.output.EUR-11.IPSL-INERIS.IPSL-IPSL-CM5A-MR.historical.r1i1p1.WRF331F.v1.mon.tasmin.v20140301			
Harvesting...			

Exploring search harvesting : Harvesting view

Harvesting View option allows to explore a dataset in a tree view. Here you can explore the metadata for datasets that include files, replicas of datasets, replicas of files and finally, ESGF services offered for explore them (by URL endpoint).

- LAS and THREDDS are services of datasets offered at replica level.
- HTTP, OPeNDAP and GridFTP are services of files offered at replica level.

```

cmip5.output1.IPSL-IPSL-CM5A-LR.historical.mon.ocean.Omon.r5i1p1.v20111119 {}
├── replicas: [4]
│   ├── [0] http://dias-esg-rp.tkl.iis.u-tokyo.ac.jp {}
│   ├── [1] http://albedo2.dkrz.de {}
│   └── [2] http://vesg.ipsl.fr {}
│       ├── id: cmip5.output1.IPSL-IPSL-CM5A-LR.historical.mon.ocean.Omon.r5i1p1.v20111119|vesg.ipsl.fr
│       └── services {}
│           ├── LAS: http://vesg.ipsl.fr/las/getUI.do?catid=2775C793BD2CBFA8D451089FC11EC4C6_ns_cmip5.output1.IPSL-IPSL-CM5A-LR.historical.mon.ocean.Omon.r5i1p1.v20111119.xml#cmip5.output1.IPSL-IPSL-CM5A-LR.historical.mon.ocean.Omon.r5i1p1.v20111119
│           ├── CATALOG: http://vesg.ipsl.fr/thredds/esgcat/4/cmip5.output1.IPSL-IPSL-CM5A-LR.historical.mon.ocean.Omon.r5i1p1.v20111119.xml#cmip5.output1.IPSL-IPSL-CM5A-LR.historical.mon.ocean.Omon.r5i1p1.v20111119
│           ├── index_node: http://esgf-node.ipsl.fr
│           └── data_node: http://vesg.ipsl.fr
│   └── [3] http://esgf-data1.ceda.ac.uk {}
├── datetime_start: 1850-01-16T12:00:00Z
├── model: [IPSL-CM5A-LR]
├── type: Dataset
├── datetime_stop: 2005-12-16T12:00:00Z
├── drs_id: [cmip5.output1.IPSL-IPSL-CM5A-LR.historical.mon.ocean.Omon.r5i1p1]
├── version: 20111119
├── timestamp: 2014-03-28T23:47:55Z
├── title: project=CMIP5, model=IPSL-CM5A-LR, Institut Pierre-Simon Laplace, experiment=historical, time_frequency=mon, modeling_realm=ocean, ensemble=r
├── realm: [ocean]
├── number_of_aggregations: 86
├── description: [IPSL-CM5A-LR model output prepared for CMIP5 historical]
├── cmor_table: [Omon]
├── experiment: [historical]
├── variable_long_name: [43]
├── dataset_id_template: [cmip5.%(product)s.%(institute)s.%(model)s.%(experiment)s.%(time_frequency)s.%(realm)s.%(cmor_table)s.%(ensemble)s]
├── instance_id: cmip5.output1.IPSL-IPSL-CM5A-LR.historical.mon.ocean.Omon.r5i1p1.v20111119
├── files: [64]
│   ├── [0] cmip5.output1.IPSL-IPSL-CM5A-LR.historical.mon.ocean.Omon.r5i1p1.v20111119.hfevapds_Omon_IPSL-CM5A-LR_historical_r5i1p1_185001-200512.nc {}
│   └── [1] cmip5.output1.IPSL-IPSL-CM5A-LR.historical.mon.ocean.Omon.r5i1p1.v20111119.rsntds_Omon_IPSL-CM5A-LR_historical_r5i1p1_185001-200512.nc {}
│       ├── replicas: [4]
│       │   ├── [0] http://dias-esg-rp.tkl.iis.u-tokyo.ac.jp {}
│       │   └── [1] http://albedo2.dkrz.de {}
│       └── services {}
│           ├── HTTPSERVER: http://albedo2.dkrz.de/thredds/fileServer/cmip5/output1/IPSL/IPSL-CM5A-LR/historical/mon/ocean/Omon/r5i1p1/v20111119/rsntds/rsntds_Omon_IPSL-CM5A-LR_historical_r5i1p1_185001-200512.nc
│           ├── GRIDFTP: gsiftp://albedo2.dkrz.de:2811/cmip5/output1/IPSL/IPSL-CM5A-LR/historical/mon/ocean/Omon/r5i1p1/v20111119/rsntds/rsntds_Omon_IPSL-CM5A-LR_historical_r5i1p1_185001-200512.nc
│           ├── OPeNDAP: http://albedo2.dkrz.de/thredds/dodsC/cmip5/output1/IPSL/IPSL-CM5A-LR/historical/mon/ocean/Omon/r5i1p1/v20111119/rsntds/rsntds_Omon_IPSL-CM5A-LR_historical_r5i1p1_185001-200512.nc
│           └── index_node: http://esgf-data.dkrz.de

```

Exploring search harvesting : Open metadata

Open metadata option allows to explore an abstract of metadata of a dataset in a table view.

Metadata	Values
CF_STANDARD_NAME	[surface_air_pressure, specific_humidity, air_temperature, eastward_wind, northward_wind]
CMOR_TABLE	[6hrLev]
DATASET_ID_TEMPLATE	[cmip5.%(product)s.%(institute)s.%(model)s.%(experiment)s.%(time_frequency)s.%(realm)s.%(cmor_table)s.%(ensemble)s]
DATETIME_START	1850-01-01T03:00:00Z
DATETIME_STOP	2005-12-31T21:00:00Z
DESCRIPTION	[IPSL-CM5A-LR model output prepared for CMIP5 historical]
DRS_ID	[cmip5.output1.IPSL.IPSL-CM5A-LR.historical.6hr.atmos.6hrLev.r5i1p1]
EAST_DEGREES	356.25
ENSEMBLE	[r5i1p1]
EXPERIMENT	[historical]
EXPERIMENT_FAMILY	[All, Historical]
FORCING	[Nat,Ant,GHG,SA,Oz,LU,SS,Ds,BC,MD,OC,AA]
FORMAT	[netCDF, CF-1.4]
INSTANCE_ID	cmip5.output1.IPSL.IPSL-CM5A-LR.historical.6hr.atmos.6hrLev.r5i1p1.v20111119
INSTITUTE	[IPSL]
LATEST	true
MASTER_ID	cmip5.output1.IPSL.IPSL-CM5A-LR.historical.6hr.atmos.6hrLev.r5i1p1
METADATA_FORMAT	THREDDS
MODEL	[IPSL-CM5A-LR]
NORTH_DEGREES	90.0
NUMBER_OF_AGGREGATIONS	8
NUMBER_OF_FILES	68
PRODUCT	[output1]
PROJECT	[CMIP5]
REALM	[atmos]

Close

Exploring search harvesting : Download Dataset - File selection window

Download Dataset... allows to manually select the files that will be put to download. In the top of window can see the id of dataset, the number of files selected, the total number of files of the dataset, the size in bytes of the sum of selected files and the total size of the whole dataset.

This windows displays a list of files and its size in bytes. You can select manually the files that you want download doing click in the check-box associated in each file in the list.


cmip5.output1.CCCma.CanESM2.historical.6hr.atmos.6hrPlev.r4i1p1.v20120618
files: (14/28) size: (11,6 GB/29,0 GB)

- psl_6hrPlev_CanESM2_historical_r4i1p1_194101010000-195012311800.nc (456,6 MB)
- psl_6hrPlev_CanESM2_historical_r4i1p1_195101010000-196012311800.nc (456,6 MB)
- psl_6hrPlev_CanESM2_historical_r4i1p1_196101010000-197012311800.nc (456,6 MB)
- psl_6hrPlev_CanESM2_historical_r4i1p1_197101010000-198012311800.nc (456,6 MB)
- psl_6hrPlev_CanESM2_historical_r4i1p1_198101010000-199012311800.nc (456,6 MB)
- psl_6hrPlev_CanESM2_historical_r4i1p1_199101010000-200012311800.nc (456,6 MB)
- psl_6hrPlev_CanESM2_historical_r4i1p1_200101010000-200512311800.nc (228,3 MB)
- ta_6hrPlev_CanESM2_historical_r4i1p1_194101010000-195012311800.nc (1,3 GB)

This window also provides the next options:

- Deselect all
- Select all
- Filter by constraints of search - select only files that satisfy the constraints of search
- Download selected - put to download the files selected in this window

When you click on **Download** selected a window asks for destination path.



Export to Metalink

To export the search to Metalink you must click on "Export to Metalink". This option is visible when harvesting of search is completed. And then a window pops up with the save options.

The files that will be include in the Metalink file are only the files that satisfy the constraints of search.



Metalink is an extensible metadata file format that describes one or more computer files available for download. It specifies files appropriate for the user's language and operating system; facilitates file verification and recovery from data corruption; and lists alternate download sources (mirror URIs). For more info: [?Metalink](#), [?Metalink-Wikipedia](#)

Exist many clients that supports Metalink: [?Aria2](#), [?GetRight](#), [?DownloadThemAll](#), [?Orbit Downloader](#), etc.

Note that if you want use a external client to download ESGF files you must configure the client for using the ESGF certificates.

Download a Search


To put the files that belongs to a search in downloads queue you must click on **Download** . . . This option is visible when harvesting of search is completed. And then a window pops up with the download options.

In this window (that you can see below) are displayed the list of datasets that satisfy the constraints of search. Each dataset have: id, description, the number of files that satisfy the search constraints with respect the total number of files and the size in disk of the selected files with respect the total size in disk of dataset.

<p>Id: cmip5.output1.IPSL.IPSL-CM5A-LR.historical.6hr.atmos.6hrLev.r3i1p1.v20110406</p> <p>Description: [IPSL-CM5A-LR model output prepared for CMIP5 historical]</p> <p>Number of files selected: 16/68 (312,8 GB/1,2 TB)</p> <p style="text-align: center;"><input type="button" value="Select files to download"/></p>
<p>Id: cmip5.output1.IPSL.IPSL-CM5A-LR.historical.6hr.atmos.6hrLev.r6i1p1.v20120526</p> <p>Description: [IPSL-CM5A-LR model output prepared for CMIP5 historical]</p> <p>Number of files selected: 16/68 (312,8 GB/1,2 TB)</p> <p style="text-align: center;"><input type="button" value="Select files to download"/></p>
<p>Id: cmip5.output1.IPSL.IPSL-CM5A-LR.historical.6hr.atmos.6hrLev.r5i1p1.v20111119</p> <p>Description: [IPSL-CM5A-LR model output prepared for CMIP5 historical]</p> <p>Number of files selected: 16/68 (312,8 GB/1,2 TB)</p> <p style="text-align: center;"><input type="button" value="Select files to download"/></p>
<p>Id: cmip5.output1.CCCma.CanESM2.historical.6hr.atmos.6hrLev.r1i1p1.v20120410</p> <p>Description: [CanESM2 model output prepared for CMIP5 historical]</p> <p>Number of files selected: 56/280 (89,8 GB/361,8 GB)</p> <p style="text-align: center;"><input type="button" value="Select files to download"/></p>


For download all files that satisfy the constraints (without manually selection) you must click on "Download" button that is in the bottom of window. Then a dialog box will be showed to confirm the download and select the destination path.

Select an option

 **Are you sure that you want to download all files that satisfy the constraints?**

Number of files to download: 184 of 824 files
Size of download: 2,5 TB

Do you want to change path of downloads?

 **The files will be downloaded at default path: /home/**** /ESGFDATA**
Do you want to change the path of the downloads?

For manually selection you may click on "Select file to Download", that displays a file selection window as explained in [Exploring search harvesting : DownloadDataset - File selection window](#)

Download of ESGF Datasets

To download ESGF Datasets you must done previously a harvesting of a search. The downloads panel is in "Download" tab.

You can add to the download queue:

- A complete search - all files of datasets that satisfy the constraints of the search (view [Download a Search](#))
- A personalized file selection of the set of datasets that satisfy the constraints of search (view [Exploring search harvesting : DownloadDataset - File selection window](#))

The most of data in ESGF require credentials to access them. To access the user must have:

1. A ESGF Account (view [ESGF Login : Obtaining credentials with ESGF Account](#))
2. This account have to be authorized to access the desired data. This authorization is done by control groups (each account can belong a many groups). Each group is authorized for download a set of data.

To read more about register in ESGF go to ([?How to register and download data from esgf](#))

The screenshot shows the 'Downloads' panel in the NetCDF (4.3) Tools application. The panel displays a list of datasets with their download progress, file size, and source. The datasets are grouped by dataset name. The progress bars are color-coded: blue for incomplete, green for completed, and gray for failed. The source information is provided for each file.

Dataset	Progress	File Size	Source
cmip5.output1.BNU.BNU-ESM.esmControl.mon.land.Lmon.r1i1p1.v20120503	25%	25,2 MB 96,8 MB	
baresoilFrac_Lmon_BNU-ESM_esmControl_r1i1p1_145001-170712.nc	25%	25,2 MB 96,8 MB	pcmdi9.llnl.gov
cmip5.output1.CCCma.CanESM2.historical.6hr.atmos.6hrLev.r1i1p1.v20120410	93%	6,0 GB 6,4 GB	
hus_6hrLev_CanESM2_historical_r1i1p1_197101010000-197112311800.	100%	1,6 GB 1,6 GB	dapp2p.cccma.ec.gc.ca
hus_6hrLev_CanESM2_historical_r1i1p1_196901010000-196912311800.	100%	1,6 GB 1,6 GB	dapp2p.cccma.ec.gc.ca
hus_6hrLev_CanESM2_historical_r1i1p1_197001010000-197012311800.	100%	1,6 GB 1,6 GB	dapp2p.cccma.ec.gc.ca
hus_6hrLev_CanESM2_historical_r1i1p1_196801010000-196812311800.	73%	1,2 GB 1,6 GB	dapp2p.cccma.ec.gc.ca
cmip5.output1.CSIRO-BOM.ACCESS1-0.historical.mon.aerosol.aero.r1i1p1.v2	61%	859,0 MB 1,4 GB	
sconcsao_aero_ACCESS1-0_historical_r1i1p1_185001-200512.nc	100%	199,0 MB 199,0 MB	pcmdi9.llnl.gov
wetpoa_aero_ACCESS1-0_historical_r1i1p1_185001-200512.nc_0	45%	90,2 MB 198,9 MB	esgnode2.nci.org.au
sconcs04_aero_ACCESS1-0_historical_r1i1p1_185001-200512.nc_0	100%	199,0 MB 199,0 MB	esgnode2.nci.org.au
wetso4_aero_ACCESS1-0_historical_r1i1p1_185001-200512.nc_0	72%	145,0 MB 198,9 MB	esgnode2.nci.org.au
wetso4_aero_ACCESS1-0_historical_r1i1p1_185001-200512.nc	15%	30,5 MB 198,9 MB	albedo2.dkrz.de
sconcss_aero_ACCESS1-0_historical_r1i1p1_185001-200512.nc	54%	108,5 MB 199,0 MB	pcmdi9.llnl.gov
od870aer_aero_ACCESS1-0_historical_r1i1p1_185001-200512.nc_0	43%	86,8 MB 198,9 MB	esgnode2.nci.org.au

The downloads panel displays a list of downloads. Each element of the list is the grouping of files by dataset. The files of each dataset can be showed or hidden.

Each element have a progress bar and file elements displays the data node from where the download is acceded.

The files can be in five states:

- No completed: When the download isn't complete. It is displayed with a blue progress bar and a percentage.
- Completed : When the download is succesful. It is displayed with a green progress bar.
- Failed : When happens some error in the current data node. It is displayed with a red progress bar.
- Checksum failed: When the validity algorithm of file failed. It is displayed with a gray progress bar with the message "CHECKSUM_FAILED".

- Unauthorized: When the user hasn't been authorized to download a file. It is displayed with a yellow progress bar with the message "UNAUTHORIZED".

psl_6hrPlev_ACCESS1-0_historical_r1i1p1_1970010106-1980010100.nc	24%	376,6 MB 1,5 GB	pcmdi9.llnl.gov
psl_6hrPlev_ACCESS1-0_historical_r1i1p1_1980010106-1990010100.nc	FAILED	380,2 MB 1,5 GB	pcmdi9.llnl.gov
ta_6hrPlev_ACCESS1-0_historical_r1i1p1_1960010106-1961010100.nc	CHECKSUM_FAILED	463,2 MB 463,2 MB	albedo2.dkrz.de
ta_6hrPlev_ACCESS1-0_historical_r1i1p1_1950010106-1951010100.nc	100%	462,0 MB 462,0 MB	albedo2.dkrz.de
psl_6hrPlev_ACCESS1-0_historical_r1i1p1_1990010106-2000010100.nc	UNAUTHORIZED	387,1 MB 1,5 GB	pcmdi9.llnl.gov

If you is logged in ESGF and there are files with "Unauthorized state" is because the groups they are associated with the user account in the federation do not have permissions for that data.

To join a group with the needed permissions for a unauthorized file, view [Join a group with the needed permissions for an unauthorized file](#)

The screenshot shows the NetCDF (4.3) Tools interface. The 'Catalog Chooser' tab is active, displaying a list of files under the URL 'http://esg.bnu.edu.cn/thredds/esgcat/1/cmip5.output1.BNU.BNU-ESM.esmControl.mon.land.Lmon.r1i1p1.v20120503'. A context menu is open over the file 'baresoilFrac_Lmon_BNU-ESM_esmControl_r1i1p1_145001-170712.nc', with options: 'download all files', 'open THREDDS catalog', 'reset', and 'remove of download list'. The 'open THREDDS catalog' option is selected, showing a list of URLs: 'http://albedo2.dkrz.de', 'http://esg.bnu.edu.cn', and 'http://pcmdi9.llnl.gov'. The main panel displays the dataset details for 'project=CMIP5, model=BNU-ESM, College of Global Change and Earth System Science, Beijing Normal University, experiment=ESM pre-industrial control, time_frequency=mon, modeling realm=land, ensemble=r1i1p1, version=20120503'. The dataset details include: Data format: netCDF, Data type: GRID, ID: cmip5.output1.BNU.BNU-ESM.esmControl.mon.land.Lmon.r1i1p1.v20120503, and RestrictAccess: esg-user. The Variables section shows 'baresoilFrac (%) = Bare Soil Fraction = area_fraction' and 'cLeaf(kg m^-2) = Carbon Mass in Leaves = leaf carbon content'. At the bottom, there are buttons for 'Open File', 'Open CoordSys', 'Open dataset', and 'Source'.

cmip5.output1.BNU.BNU-ESM.esmControl.mon.land.Lmon.r1i1p1.v20120503	56%	54,7 MB 96,8 MB	
baresoilFrac_Lmon_BNU-ESM_esmControl_r1i1p1_145001-170712.nc	56%	54,7 MB 96,8 MB	pc
cmip5.output1.BNU.BNU-ESM.esmControl.mon.land.Lmon.r1i1p1.v20120410	93%	6,0 GB 6,4 GB	
hus_6hrPlev_ACCESS1-0_historical_r1i1p1_197001010000-197012311800.nc	100%	1,6 GB 1,6 GB	d
hus_6hrPlev_ACCESS1-0_historical_r1i1p1_196901010000-196912311800.nc	100%	1,6 GB 1,6 GB	d

ESGF Login : Obtaining credentials with ESGF Account

Harvesting Downloads **Login**

You are logged.
Remaining time of validity of credentials: days:1, 15:4:24

OpenID url: << Another index node >>

- euclipse1.dkrz.de
- esgf-data.dkrz.de
- esgf.nccs.nasa.gov
- esg-datanode.jpl.nasa.gov**
- esg2.nci.org.au
- esg01.nersc.gov
- esg.ccs.ornl.gov
- << Another index node >>

Join a group with the needed permissions for a unauthorized file