

Table of Contents

How to add Neptuno facilities to WRF4G	2
Neptuno Running Options	2
Neptuno Data Repository	3
Seawing Package Version	3

How to add Neptuno facilities to WRF4G

WRF4G uses [DRM4G](#) to access to different Distributed Resource Managements (DRM) such as:

- PBS/Torque
- SGE
- FORK
- LoadLeveler
- SLURM -> **neptuno**

In order to add new resources, you need to edit [Computing Resources](#) section in the [framework4g.conf](#) file, which is located under `$HOME/WRF4G/etc` directory. The file has to contain one resource per line with the format:

```
resource_name = attributes
...
resource_name = attributes
```

where:

- **resource_name**: It is the name of the CR.
- **attributes**: They are the static attributes of the CR. The syntax is:


```
<scheme>://<username>@<host:port>?<query>
```

 - **scheme**: URL schemes available are "ssh" and "local".
 - **ssh**: In order to connect to remote resource via SSH
 - **local**: In order to use a local resource
 - **username**: user name on the resource
 - **host**: host name
 - **port**: host port. By DEFAULT it is 22
 - **query**: contains additional information of computing resources. The query string syntax is:
 - `key1=value1;key2=value2;key3=value3`

The keys available are:

- **LRMS_TYPE**(mandatory): Type of LRMS system (**neptuno**)
- **NODECOUNT**(mandatory): Maximum number of job slots for a resource.
- **SSH_KEY_FILE**(optional): It defines the key file for "ssh" connection. By DEFAULT it is `$HOME/.ssh/id_rsa`.
- **TEMP_DIR**(optional): Temporary directory on the resource to store data. By DEFAULT it is `$HOME`. **TEMP_DIR** path must be absolute.
- **RUN_DIR**(optional): Temporary directory used to run WRF Model on the resource. By DEFAULT it is `$HOME`. **RUN_DIR** path must be absolute.

Example of configuration:

```
neptuno = ssh://userid@IP_neptuno?LRMS_TYPE=neptuno;NODECOUNT=1500
```

If you want to configure Neptuno facilities using **ssh** protocol, you need to set up SSH login without *password* (see [Appendix B](#)) between **MACC cluster** and **Neptuno**, and **vice-versa**.

After modifying `ComputingResources` section, WRF4G takes few seconds in order to update the changes

Neptuno Running Options

[Running Options](#) section is defined in [resources.wrf4g](#) file and its variables of interest are:

- **NP** is the number of processors requested in a parallel job.
- **PPN** indicates the number of processors available per node.

Example of configuration:

```

REQUIREMENTS = 'PPN = 16'
NP = 16

```

NP = 16 and REQUIREMENTS = 'PPN = 16' which means 16 processors on one node.

Neptuno Data Repository

In addition, you need to update WRF4G_BASEPATH, WRF4G_DOMAINPATH, WRF4G_INPUT and WRF4G_APPS variables, which are defined in [resources.wrf4g](#) file. Due to the fact that these variables may point to other machines by default. See [running environment](#) for more information as well.

Example of configuration:

```

WRF4G_BASEPATH="rsync://id_user_neptuno@IP_neptuno/home/users/id_user_neptuno/wrf_repos/projects/seawind_ncep/data/raw"
WRF4G_DOMAINPATH="/home/users/id_user_neptuno/wrf_repos/projects/seawind_ncep/domains"
WRF4G_INPUT="/home/users/id_user_neptuno/wrf_repos/DATA"
WRF4G_APPS="rsync://id_user_neptuno@IP_neptuno/home/users/id_user_neptuno/wrf_repos/apps"

```

Seawing Package Version

[Package Version](#) section is defined in [resources.wrf4g](#) file.

- **WRF4G_VERSION** : WRF4G version to use. A file WRF4G-[WRF4G_VERSION].tar.gz must exist under \$HOME/etc/templates.
- **WRF_VERSION**: WRFbin version to use. A file WRFbin-[WRF_VERSION].tar.gz must exist under \$WRF4G_APPS.

And for this experiment, we are going to use:

```

WRF4G_VERSION="1.0"
WRF_VERSION="3.1.1_r832INTEL_OMPInew"

```