

Wikiprint Book

Title: JRE Installation

Subject: TracMeteo - udg/ecomms/RPackage/prerequisites

Version: 22

Date: 08/09/2022 01:07:17 AM

Table of Contents

| | |
|--|----------|
| JRE Installation | 3 |
| Linux users | 3 |
| Windows / Mac users | 3 |
| Installing the rJava package | 3 |
| Linux | 3 |
| Mac OS X | 4 |
| Windows | 4 |
| Find out the java version used by R | 4 |

JRE Installation

Installation of the Java Platform, Standard Edition Runtime Environment (JRE), allows you to run Java programs on your PC and as you browse the Internet. The `ecomSUDG.Raccess` package needs the JRE in order to use the powerful capabilities of the [?netCDF Java Library](#).

It is very likely that JRE is already installed on your computer, but just in case it is not, here are some instructions on how to get it.

Linux users

To find out if JRE is installed in your machine, and in negative case to get instructions on how to install it, please refer to [?this link](#)

Windows / Mac users

Click on the link below to download the JRE installer and perform the installation procedure by keeping the default installer settings. For Windows users, please be sure that you have downloaded the 32-bit JRE installer as indicated below.

[?JRE installer download link](#) (version 7 update 60):

| Java SE Runtime Environment 7u60 | | |
|---|-----------|---|
| You must accept the Oracle Binary Code License Agreement for Java SE to download this software. | | |
| <input type="radio"/> Accept License Agreement <input checked="" type="radio"/> Decline License Agreement | | |
| Product / File Description | File Size | Download |
| Linux x86 | 31.55 MB | jre-7u60-linux-i586.rpm |
| Linux x86 | 46.18 MB | jre-7u60-linux-i586.tar.gz |
| Linux x64 | 32.06 MB | jre-7u60-linux-x64.rpm |
| Linux x64 | 44.81 MB | jre-7u60-linux-x64.tar.gz |
| Mac OS X x64 | 48.52 MB | jre-7u60-macosx-x64.dmg |
| Mac OS X x64 | 44.5 MB | jre-7u60-macosx-x64.tar.gz |
| Solaris x86 | 52.17 MB | jre-7u60-solaris-i586.tar.gz |
| Solaris x64 | 16.12 MB | jre-7u60-solaris-x64.tar.gz |
| Solaris SPARC | 54.92 MB | jre-7u60-solaris-sparc.tar.gz |
| Solaris SPARC 64-bit | 18.16 MB | jre-7u60-solaris-sparcv9.tar.gz |
| Windows x86 Online | 0.88 MB | jre-7u60-windows-i586-iftw.exe |
| Windows x86 Offline | 28.04 MB | jre-7u60-windows-i586.exe |
| Windows x86 | 39.94 MB | jre-7u60-windows-i586.tar.gz |
| Windows x64 | 29.55 MB | jre-7u60-windows-x64.exe |
| Windows x64 | 41.64 MB | jre-7u60-windows-x64.tar.gz |

Installing the `rJava` package

[?rJava](#) is a R package providing a low-level interface to Java from R. If Java is installed and adequately configured in your computer, the `rJava` package will be automatically downloaded if not present when installing the `ecomSUDG.Raccess` package, as any other package dependency.

Therefore, in principle you should not worry about this and could skip this section. But just in case something related to `rJava` goes wrong during the installation, please bear in mind the following information:

Once Java is installed in your machine, in most cases the following call from R should do the trick:

```
> install.packages("rJava")
```

Linux

Linux users can alternatively use the *apt-get* choice from the terminal:

```
~$ apt-get install r-cran-rjava
```

(In case of doubts, there is a recent discussion on both choices [?at this link](#) that you may find helpful).

You can also find useful information about the installation and configuration of openJDK in [?this thread](#) of the Ubuntu forum.

Mac OS X

Mac OS X comes with Java pre-installed, so everything should ?just work?.

Windows

For Windows 7, you can find some quick advice on how to get up and running with R + rJava [?at this link](#)

If an error likes this one appears on your R console:

```
Error : .onLoad failed in loadNamespace() for 'rJava', details:
  call: inDL(x, as.logical(local), as.logical(now), ...)
  error: unable to load shared object 'C:/Users/antonio/Documents/R/win-library/3.2/rJava/libs/x64/rJava.dll':
  LoadLibrary failure:  %1 no es una aplicación Win32 válida.

Error : package 'rJava' could not be loaded
```

it can be due to a misconfiguration of `JAVA_HOME` environment variable.

Please check that the corresponding value points to the **correct Java version and bit architecture** (32 or 64).

```
> Sys.getenv("JAVA_HOME")
```

You can remove from system environment and restart R or remove from R session:

```
> if (Sys.getenv("JAVA_HOME") != "")
+   Sys.setenv(JAVA_HOME="")
```

or you can force the JVM ():

```
> Sys.setenv(JAVA_HOME="C:\\Program Files (x86)\\Java\\jdk1.7.0\\jre")
```

and check which JVM is using rJava:

```
> .jinit()
> .jcall("java/lang/System", "S", "getProperty", "java.vendor")
[1] "Oracle Corporation"
> .jcall("java/lang/System", "S", "getProperty", "java.runtime.version")
[1] "1.7.0-b147"
> .jcall("java/lang/System", "S", "getProperty", "os.arch")
[1] "x86"
```

Find out the java version used by R

Once rJava is installed, you may want to know the characteristics of the java version used by R:

```
library(rJava)
.jinit()
[1] 0
jvm <- .jnew("java.lang.System")
jvm.props <- jvm$getProperties()$toString()
```

```
strsplit(gsub("\\{(.*)}", "\\1", jvm.props), ", ")[1]
```